

INFIRAY OUTDOOR HYBRID SERIES

MULTIFUNCTION THERMAL OPTIC

First introduced as the powerful combination of a thermal weapon sight and a thermal clip-on unit, the HYBRID line-up continues to evolve with specialized models, top-performing sensors, and an advanced feature set designed for technical shooters. The combination of the HYBRID's low-distortion orthoscopic eyepiece and a 1.03-inch large-format 2560×1920 display provides comfortable viewing, a sharp image, and massive eye relief. The HYBRID also unlocks advanced features such as compatibility with a 1,000 yard laser rangefinder, a custom ballistic reticle generator, wireless remote, and an onboard ballistic solver. This year, the HYBRID family expands with the addition of the 75 mm model (HYH75W), optimized for long-range shooters and the 50 mm 90 Hz model (HYL50W), optimized for smooth motion and fast moving targets.



Infiray Outdoor



RICO HYBRID SERIES		HYL50W	HYH50W	HYH75W
SENSOR				
Resolution	384×288		640×512	
Pixel Size	17 μm		12 μm	
Frame Rate	50hz / 90hz		50hz	
Sensor Sensitivity	≤25 mK			
Image Processing	MATRIX III			
Core	InfiRay Micro II 384		InfiRay Micro II 640	
OPTICS				
Objective Lens	50 mm f/1.0			75 mm f/1.0
Magnification	3×			4×
Digital Zoom	8×			
Field of View	7.5° × 5.6°		8.8° × 6.6° 5.9° × 4.4°	
Detection Range	2000 Yards		2400 Yards 3600 Yards	
Display Type	1.03-inch Large-format AMOLED			
Display Resolution	2560×1920			
Color Palettes	White Hot, Black Hot, Red Hot, Iron Hot, Rainbow, Outline*			
Reticle Types	9 (7 Static, 1 DIY, 1 BDC)			
Reticle Colors	Black, White, Red, Green, Blue			
Mounting System	Picatinny MIL-STD 1913 Rail			
P.I.P	Yes			
Rangefinder	ILR-1000-2 LRF (Optional/Not Included)			
Eye Relief	60 mm			
Diopter Range	-4 to +2			
ELECTRONICS				
Onboard Recording	Video, Recoil-activated Video, and Image			
Onboard Storage	64 GB			
Wireless Connectivity	Video and Image via App			
Data/Power Connector	USB-C			
Power Supply	USB-C External, IBP-1H Li-Ion Battery Pack (6+ Hours Each)			
Start Up Time	<10 Seconds, Instant from Standby			
PHYSICAL				
Size	11.02" × 3.03" × 2.99"			12.20" × 4.13" × 3.58"
Weight	30.01 Oz		40.5 Oz 45.08 Oz	
ENVIRONMENTAL/WARRANTY				
Warranty	5 Years			
Housing Material	Magnesium		Aluminum Magnesium	
Ingress Protection	IP67			
Operation Temperature	-4°F~122°F			
Max. Recoil	1000 G/s ² (300 Win./7mm Mag)			

*Outline color palette not currently available on HYL50W

REGISTRATION: irayusa.com/register
WARRANTY: irayusa.com/warranty
SUPPORT/SERVICE: irayusa.com/support

NOTE: These products may be subject to export and foreign trade control laws of the United States and may not be exported without prior approval of the U.S. Department of State. Learn more at irayusa.com/ITAR. The thermal images shown are for illustrative purposes only and may vary in real world usage. Specifications are subject to change without notice. For the most up-to-date specs, go to irayusa.com. Not responsible for typographical errors. Ver 1.00 - 202405

Multiple Lens Options

Ultra-fast high-performance germanium 50 mm or 75 mm f/1.0 objective lens.

IBP-1H Battery Pack

Field-swappable lithium battery offers 6+ hours of run time (varies by model and settings).

2560×1920 AMOLED Display

Large-format display and magnified eyepiece create unmatched eye relief.

HYL50W

90 Hz / 50 Hz Modes

HYL50W is the industry's first 90 Hz thermal sight. It can also run in a 50 Hz mode for increased battery life.

Recoil-activated Video

30-second clips automatically record before and after a shot.

LRF Compatible

Plug-and-play compatibility with ILR-1000-2 laser rangefinding module.

Advanced Recoil-mitigating Picatinny STD-1913 Mount

Isolates recoil for improved accuracy and long-term durability.



All models in the HYBRID series can be used as a clip-on thermal in front of a day scope (with magnification up to 10x). Additionally, all HYBRID models are compatible with the ILR-1000-2 Laser Rangefinder, which provides real-time ranging data on the display and can even dial a firing solution based on user-supplied drop values.



To visit the product webpage, scan the QR code or go to irayusa.com/hybrid

iRAYUSA

2601 SH 121, Building 3
Suite #306
Lewisville, TX 75056

800-769-7125
682-499-0047
info@irayusa.com